

IP NETWORK CAMERAS	
SNC-B2315	NEW! Samsung IP Camera, Low light, Dual voltage, 1/3" Color DSP, 540TV Lines, WDR, On Board storage with SD Card Slot, True Day/Night 0.02 lux Minimum scene illumination, IP protocol, supported by Samsung Net-I software
SNC-B5395	NEW! Samsung IP Vandal Resistant Fixed Dome Camera, IP66, Low light, Dual voltage, 1/3" Color DSP, 540TV Lines, w/ 2.9-10mm auto iris lens, On Board storage with SD Card Slot, True Day/Night 0.02 lux Minimum scene illumination, IP protocol, supported by S
SNC-M300	NEW! Samsung Mega Pixel Network Camera, CMOS with 3 Mega Pixel Resolution, MPEG-4 & motion JPEG dual encoding, simultaneous streaming, 1.3 / 2 / 3 mega pixel resolution (selectable), Video motion detection, Pre/post alarm image buffering, DDNS support, Po
COLOR CAMERAS	
SCC-131B	Samsung Switch Programmable DSP Camera, 520TV Lines, 1/3", 0.3 Lux, 12VDC, 24VAC, C/CS Mount, DC/Video, Built in anti-Ground loop XFMR, S/N of 50 dB, 3.0 Watts
DAY / NIGHT CAMERAS	
SCC-B2311	Samsung 1/3" Sony Super HAD CCD, Super High Resolution, Electronic Day/Night Function. 540TV Lines, 0.0009 lux @15IRE. Digital Noise Reduction, Built-in Anti- Ground Loop XFMR, Dual Voltage, 12Vdc or 24Vac
SCC-B2391	Samsung 1/3" Sony Super HAD CCD, High Resolution True Day/Night Camera. 570 Lines BW, 540TV Lines in color. 0.06 lux BW, 0.3 color. Dual Voltage, 12Vdc or 24Vac
SCC-B2315	Samsung DSP 1/3" Super HAD CCD, Multi-Language On-Screen Menu, Wide Dynamic Range X64, True Day/Night, lines: 540 TV Lines Color, 570 TV Lines B&W, up 0.0005 Lux B&W and 0.0005 lux Color@ 15 IRE, Motion detection with alarm output, Super HAD, 24 privacy z
MOTORIZED ZOOM CAMERAS	
SCC-C4301	Samsung IC Series Camera, Low light, Dual voltage, 1/4" Color DSP, 480TV Lines, Motorized Zoom 22X optical (3.6-79.2 mm) , 10X Digital Zoom (X220), 0.02 lux Minimum scene illumination, RS485 Remote control / Rear Control of Zoom/Focus
SCC-C4335	Optical, 16X Digital Zoom(X512), Motion Detection, 0.005 Lux for Color, 0.002 Lux for B&W, Smart Focus Function
SCC-RC130	Zoom, focus, OSD menu, wired remote controller for one Zoom Cameras. Functions up to 100mts (330ft)
MOTORIZED ZOOM, HIGH IMPACT DOME CAMERA	
SCC-931T	Samsung IC Series, High Impact Dome, fix 1/4" Color DSP camera. 480TV Lines, 0.01 lux Minimum scene illumination, 24VAC/12VDC, 12X (3.6-43.2 mm) Motorized Zoom w/10X Digital Zoom (X120), PIP, Motion detection, RS485 Remote control / Internal Manual Control
SADT-101WM	Wall Mount for SCC-931T, white, Indoor/Outdoor
SCC-C9302	Samsung IC Series, High Impact Dome, fix 1/4" Color DSP camera. 480TV Lines, WDR, Day/Night, 0.2 lux color/ 0.07 B&W Minimum scene illumination, 24VAC/12VDC, 12X (3.6-43.2 mm) Motorized Zoom w/10X Digital Zoom (X120), 8 privacy zones, PIP, Motion detectio
SCC-C9302F	Samsung IC Series, High Impact Dome, fix 1/4" Color DSP camera. 480TV Lines, WDR, Day/Night, 0.2 lux color/ 0.07 B&W Minimum scene illumination, 24VAC/12VDC, 12X (3.6-43.2 mm) Motorized Zoom w/10X Digital Zoom (X120), 8 privacy zones, PIP, Motion detectio
SADT-102WM	Wall Mount for SCC-C9302, white, Indoor/Outdoor

BULLET CAMERAS, IR CAMERAS	
GV-CLRIR	Day/Night, 1/4" Color, 380TV Lines 1 Lux with IR Illumination, 12 LEDs. Sunshield & PS included, 3.6mm lens, Weather resistant IP65
GV-BCC825	1/3" SONY SUPER HAD CCD 380K pixels, Color bullet Camera, 520TV Lines, 0.3 LUX (F 1.2) LED OFF, 0 LUX LED ON, with sunshield and mounting bracket. Dimensions: 2.5" x 4.5", 24 IR LEDs, 12 Vdc 500mA (power supply is included). Operation temp:-10°C to +50°
SCC-B9221	SAMSUNG 1/3" SONY SUPER HAD CCD 380K pixels, Color bullet Camera, 480TV Lines, 0.3 LUX, 12 Vdc. Bracket included. Operation temp:-10°C to +50°C, 3.8-9.5mm auto iris lens, Weather resistant IP66
SCC-B9371	SAMSUNG 1/3" SONY SUPER HAD CCD 380K pixels, True Day/Night Bullet Camera, 540TV Lines, 0.5 LUX (F 1.2) LED OFF, 0 LUX LED ON, 36 IR LEDs, 24VAC/12VDC, Bracket included. Operation temp:-10°C to +50°C, 3.8-9.5mm auto iris lens, Weather resistant IP66
SCC-B9374	SAMSUNG 1/3" SONY SUPER HAD CCD 380K pixels, True Day/Night IR Dome Camera, 540TV Lines, 0.5 LUX (F 1.2) LED OFF, 0 LUX LED ON, 18 IR LEDs, 24VAC/12VDC, 3-Axis Gimbal Bracket. Operation temp:-10°C to +50°C, 3.8-9.5mm auto iris lens, Anti-Vandal and Weathe
STANDARD FIXED DOMES	
GV-MDC	3.5" Mini Dome, 1/4" Color CCD, 380TV Lines, 1 lux F2.0, 3.6 mm lens. 12 VDC w/Power Supply
SCC-B5313	Samsung 1/3" Sony Super HAD IT CCD, 540TV Lines, 0.002 Lux, Electronic Day/Night Function, 24Vac/12Vdc includes 3.0mm lens, ATW, BLC, AGC, ELC, DNR, No Power Supply
SCC-B5203	Samsung Color 1/3" Super HAD IT CCD, 520TV Lines, 0.5 Lux, 12Vdc includes 3mm lens, ATW, BLC, AGC, ELC, No Power Supply. Limited Quantities Available
SCC-B5203S	Samsung Color 1/3" Super HAD IT CCD, 520TV Lines, 0.5 Lux, 12Vdc includes 3mm lens, ATW, BLC, AGC, ELC, No Power Supply. Silver. Limited Quantities Available
VARIFOCAL DOME CAMERAS	
GV-VMDC	NEW! 1/4" Color CCD Standard indoor mini Dome,380TV Lines, 1 lux color, DC Auto Iris VARIFOCAL lens f=4~9mm. 24 Vac/ 12 Vdc
GV-VD7305	4" indoor Dome, True Day/Night 1/3" Super HAD CCD, 0.5 lux color, 0.03 lux B&W, 580 TV Lines B&W, 550TV Lines Color, Auto Iris VARIFOCAL lens f=2.9~10.0mm. 24 Vac/ 12 Vdc
SCC-B5352	Samsung 1/3" Sony Super HAD IT CCD, Electronic Day/Night, Vari-Focal, 540TV Lines, 2.5-6mm Auto Iris Lens, Digital Noise Reduction,Dome Camera with Tri-Axis, 24Vac/12Vdc
SCC-B5353	Samsung 1/3" Sony Super HAD IT CCD, Moving Filter True Day/Night Vari-Focal, 540TV Lines, 2.5-6mm Auto Iris Lens, Digital Noise Reduction, Dome Camera with Tri-Axis, 24Vac/12Vdc
SCC-B5354	Samsung 1/3" Sony Super HAD IT CCD, Electronic Day/Night ,Vari-Focal, 540TV Lines, 2.9-10mm Auto Iris Lens, Digital Noise Reduction,Dome Camera with Tri-Axis, 24Vac/12Vdc
SCC-B5355	Samsung 1/3" Sony Super HAD IT CCD, Moving Filter True Day/Night Vari-Focal, 540TV Lines, 2.9-10mm Auto Iris Lens, Digital Noise Reduction,Dome Camera with Tri-Axis, 24Vac/12Vdc
SCC-B5393	Samsung 1/3" Sony Super HAD IT CCD Anti-Vandal IP66, Color, DNR, Moving Filter True Day/Night Vari-Focal, 540TV Lines, 2.5-6mm Auto Iris Lens, Dome Camera with Tri-Axis, 24Vac/12Vdc
SCC-B5395	Samsung 1/3" Sony Super HAD IT CCD Anti-Vandal IP66, Color, DNR, Moving Filter True Day/Night Vari-Focal, 540TV Lines, 2.9-10mm Auto Iris Lens, Dome Camera with Tri-Axis, 24Vac/12Vdc
SADT-102WM	Wall Mount for SCC-B5393 and SCC-B5395, white, Indoor/Outdoor

TRANSFORMERS & POWER SUPPLIES	
GV-TRAN-24-20LED	24VAC, 20 VA, Class II Plug in transformer, LED Power Indicator on Unit
GV-TRAN-24-40LED	24VAC, 40 VA, Class II Plug in transformer, LED Power Indicator on Unit
GV-TRAN-12-500DC	12VDC, 500ma, Plug in transformer, Screw Terminals
GV-M2444UL	24 VAC, at 3.5 amp/ 4 fused outputs / UL listed Commercial CCTV equipment (UL 2044)
GV-M2448UL	24 VAC at 4.0 amp / 8 fused outputs / UL listed Commercial CCTV equipment (UL 2044)
GV-M24816UL	24 VAC at 8.0 amp / 16 fused outputs / UL listed Commercial CCTV equipment (UL 2044)
GV-M1234	12 VDC at 3.0 amp / 4 fused outputs / UL listed, battery charger built in, 9" X 10" X 4.75"
CAMERA MOUNTS AND HOUSINGS	
GV-HOU3512	IP66, Indoor/Outdoor Housing with Mounting bracket. 16" Total length, Extruded Aluminum Construction Body
GV-HOU3512HB	IP66, Indoor/Outdoor Housing, Heater & Blower. 24 Vac. With Mounting bracket, 16" Total length, Extruded Aluminum Construction Body
GV-OP5112	Empty Ceiling Mount Dome for Chassis cameras. Acrylic 12" tinted Dome. 360° view. For 1.5" EMT
GV-IDWMBG	6.25" Beige Indoor Camera Mount with Adjustable Head. Plastic
GV-IDWMBG-5	Indoor camera mount, 4.25" long when in ceiling, 3.5" long when in wall. Metal and Plastic
LENSES	
GV-2.8-12ADC	1/3" 2.8-12mm Vari-focal F0.95 – C, F0.95 - T360, DC auto iris, CS Mount, Metal mount, Glass Optics
GV-3.5-8ADC	1/3" 3.5 - 8mm Vari-Focal F1.4 - 64 Auto Iris DC CS Metal Mount, plastic body, Glass Optics
GV-5-100ADC	1/3", 1/2" 5-100mm Vari-focal F1.4-T360, DC auto iris, Metal mount, Glass Optics
SMART DOME™ SYSTEMS	
SCC-C6403	Samsung IC Series Smart Dome, 350 Degree Panning, 1/4" Ex-view CCD, True Day/Night, X32 optical Zoom lens, Built-in 10X Digital Zoom, RS-485, 0.01 Lux Color, 0.001 Lux B&W(sens up x128), 0-90 Degree Tilting, Motion Detection, Alarm in 4Ch, Alarm out 3Ch,
SCC-641	Samsung IC Series Smart Dome, Hi-Res, 480TV Lines, High Sensitivity With a Minimum Scene Illumination of 0.02 Lux, 22X optical zoom plus 10X Digital Zoom, 240 degree/sec, RS-485 Control, 3 Tours, 128 individually programmable presets, Picture in picture,
SCC-C6407	Samsung IC Series Smart Dome, 1/4" Ex-view CCD, True Day/Night, WDR, X32 optical Zoom, built-in 10X Digital Zoom lens, RS-485 0.005 Lux Color, 0.002 Lux B&W(sens up x160), 360 Degree Endless Rotation, Motion Detection, Alarm in 4Ch, Alarm out 3Ch, 480TV L
SSC-5000	NEW! Samsung Multi Protocol, Touch Screen TFT Color LCD System Keyboard, (Smart Domes Series, Motorized Zoom Lens Cameras and Anti-Vandal Dome cameras,) 3D joystick, allows the user to control the cameras' pan, tilt and zoom all with one hand. RS-485 loop
SSC-1000	Samsung Controller for IC Series Cameras (Smart Domes Series, Motorized Zoom Lens Cameras and Anti-Vandal Dome cameras), RS-485 loop up to 4000ft (max total distance), LCD Screen, PTZ Control, Tours, Scan, Sequence, Presets

HOUSING FOR YOUR SMART DOME IF NEEDED	
SBR-100DCM	Indoor Ceiling Mount Bracket for recess application of all metal housing
SHG-120	Metal Indoor Housing for SCC-641/SCC-C6403/SCC-C6407. Supports 70 lb/32Kg. Requires wall or pendant mount
SHG-220	Metal Outdoor Housing-Heater/Blower for SCC-641/SCC-C6403/SCC-C6407, supports 97 lb/44Kg, Fan operating at 45 C or higher, Heater 10 C or less. Requires wall or pendant mount. Heater will require 1.3 Amps
WALL MOUNT FOR YOUR SMART DOME IF NEEDED	
SADT-100WM	Wall Mount for SCC-641/SCC-C6403/SCC-C6407, Indoor/Outdoor. Requires a housing
SADT-100CM	Ceiling Mount for SCC-641/SCC-C6403/SCC-C6407, Pendant. Requires a housing
POLE MOUNT ADAPTER FOR YOUR SMART DOME IF NEEDED	
SADT-100PM	Pole Mount for SCC-641/SCC-C6403/SCC-C6407, use with SADT-100WM Wall mount
SADT-110CM	Corner Mount for SCC-641/SCC-C6403/SCC-C6407, use with SADT-100WM Wall mount
POWER TRANSFORMER FOR SMART DOMES	
GV-TWCS	Transformer 24VAC 4A (100VA) for SCC-641/SCC-C6403/SCC-C6407 needed for outdoor Housing, 8.5"H X 7.5"W X 3.5"D cabinet
CRT COLOR MONITORS	
SMC-150F	Samsung 15" Flat CRT Color Monitor, 400 lines. Two BNC In/out channels, two in/out Audio jacks, Metal Case, VCR input (BNC video and RCA audio). OSD, NTSC/PAL
SMC-152F	Samsung 15" Flat CRT Color Monitor, 400 lines, Four Video Inputs with Sequential Switcher, 4 Audio inputs, Metal Case, VCR input (BNC video and RCA audio). OSD, Comb Filter, NTSC/PAL
SMC-213	Samsung 21" Ultra Slim CRT Color Monitor, 450 lines, Audio, Metal Case, Industrial Grade, Two Video Inputs A/B, Looping
TFT/LCD COLOR MONITORS	
SMT-1721	550TV Lines, 1000:1 Contrast Ratio, 5ms Response time, Built-in Speakers. (Price reduction for this item will be effective October)
SMT-1921	550TV Lines, 1000:1 Contrast Ratio, 5ms Response time, Built-in Speakers. (Price reduction for this item will be effective October)
SMT-1722	NEW! Samsung 17" LCD TFT Monitor, 600 Lines Ultra High Resolution, Built for Security, Built-in Power Supply, 2 BNC in/out, VGA input, Tempered Glass, 1280X1024, 1000:1 Contrast Ratio, 5ms Response time, Built-in Speakers. DNle, Audio with VGA
SMT-1922	in/out, VGA input, Tempered Glass, 1280X1024, 1000:1 Contrast Ratio, 5ms Response time, Built-in Speakers. DNle, Audio with VGA
SMT-3211	Samsung 32" Large Format LCD Display, Built for Security, Built-in Power Supply, Multiple Inputs: D-Sub, RS232C cable, DVI-D, USB 2.0, S-Video, CVBS Video, BNC. Extended Video Wall Format, Pivot Technology, Picture in Picture and Picture By Picture, Anti
SMT-4011	Samsung 40" Large Format LCD Display, Built for Security, Built-in Power Supply, Multiple Inputs: D-Sub, RS232C cable, DVI-D, USB 2.0, S-Video, CVBS Video, BNC. Extended Video Wall Format, Pivot Technology, Picture in Picture and Picture By Picture, Anti
VIDEO PLUS™ - TWISTED PAIR SENDERS	
GV-VB-59SP	Two Wire T/R, Video Balun, Surge protected, tool-less Terminal/BNC Connector, up to 2500 Feet Monochrome, 2200 Feet Color on CAT 5 Cable. No screws, no tools needed
GV-AVBT	Active Twisted Pair Video Transmitter up to 6000 ft with GV-AVBR and up to 3000ft with VB-59P on Cat5, Built-in Surge protection, 12V-24V DC/AC, 12V DC Power Supply Included

GV-TPC16PS	NEW! Unshielded Twisted Pair 16 Channel Hub with 24VAC power to each channel and distribution of control data to field modules. 8 amp total available power with maximum of 1.1 amp for any individual channel
GV-TPC16	NEW! Unshielded Twisted Pair 16 Channel Hub
GV-TPCV2	NEW! Unshielded Twisted Pair module transmits video over 1 pair Cat 5 cable and receives power from GV-TPC16PS over 2 pair of Cat 5 cable
GV-TPCV3	NEW! Unshielded Twisted Pair module transmits video over 1 pair Cat 5 cable and receives power from GV-TPC16PS over 3 pair of Cat 5 cable
GV-TPCVPD	NEW! Unshielded Twisted Pair module transmits video over 1 pair Cat 5 cable and receives power from GV-TPC16PS over 2 pair of Cat 5 cable and data over 1 pair Cat 5 cable
GV-TPCVPT	NEW! Unshielded Twisted Pair module transmits with amplifier to transmit video over up to 6000 feet over 1 pair Cat 5 cable includes 12VAC power supply
VCR'S	
SRV-960A	Samsung 24 Hour Real Time Recorder, 960 hr time lapse, Jog Shuttle, 300/350 Lines, Alarming, RS-232 Option, 6H; 18H; 30H; 72H; 120H; 168H; 240H; 480H and 960H
QUADS AND MULTIPLEXERS	
GV-Q4CHRTC-BR	Color Real time Quad, On Screen Display, 720 X 480 res, Time date & ID stamp, video loss det, 16 mill colors
GV-CMP163R	Color, Sixteen Channel Triplex digital Multiplexer, 720 X 480 Res, Alarming, RS-232 remote control, Video Loss, Zoom, PIP, Motion detection. Main, Spot and VCR BNC outputs. Simultaneous display of VCR replay and live view

STANDALONE DIGITAL VIDEO RECORDERS	
SHR-5080	NEW! Samsung DVR, 8 Ch, MPEG4 compression, Dual Codec, 120 ips record, real time viewing, triplex, USB port, 4 Ch Audio, 250GB Hard drive
SHR-5082	Samsung DVR, 8 Ch, MPEG4 compression, Dual Codec, 120 ips record, real time viewing, triplex, USB port, 4 Ch Audio, 250GB Hard drive. Built in DVD-RW
SHR-5160	NEW! Samsung DVR, 16 Ch, MPEG4 compression, Dual Codec, 120 ips record, real time viewing, triplex, USB port, 4 Ch Audio, 250GB Hard drive
SHR-5162	Samsung DVR, 16 Ch, MPEG4 compression, Dual Codec, 120 ips record, real time viewing, triplex, USB port, 4 Ch Audio, 250GB Hard drive. Built in DVD-RW
SHR-4081	Samsung DVR, 8 Ch, MPEG4 compression, 240 ips record, real time viewing, triplex, 2 USB ports, 4 Ch Audio, 160G Hard drive. IEE-1394 port
SHR-4160	Samsung DVR, 16 Ch, MPEG4 compression, 360 ips record, real time viewing, triplex, 2 USB ports, 8 Ch Audio, 160G Hard drive. IEE-1394 port
SHR-8162	Samsung DVR, 16 Ch, MPEG4 compression, 480 ips record, real time viewing, triplex, 2 USB ports, 8 Ch Audio, 250G Hard drive. IEE-1394 port.
WSR-16120	16ch DVR, Pentaplex, Live Display/Record Rate: 480/120fps, 2 USB2.0, RS-422/485 including VGA Output
WSR-16240	16ch DVR, Pentaplex, Live Display/Record Rate: 480/240fps, 2 USB2.0, RS-422/485 including VGA Output
WSR-16480	16ch DVR, Pentaplex, Live Display/Record Rate: 480/480fps, 2 USB2.0, RS-422/485 including VGA Output, 16ch Audio
STANDALONE DIGITAL VIDEO RECORDERS	
GV-DVR1042-250	DVR 4channel, MPEG4 Compression, Triplex, 120 IPS at CIF resolution, 1 USB port, CDRW, 250GB Hard Disk Drive, Web Browser and USB Mouse Control
GV-DVR1042-500	DVR 4channel, MPEG4 Compression, Triplex, 120 IPS at CIF resolution, 1 USB port, CDRW, 500GB Hard Disk Drive, Web Browser and USB Mouse Control. For Greater Hard Drive Versions Call for Quote
GV-EM412DD-80	4 ch Stand alone, 720X480 live display, Removable empty HD tray, 80GB Hard Drive, Compact Flash slot, Pseudo MPEG-4 recording, 120 ips at 360X240. Jog/Shuttle, Continuous, alarm or Motion Recording. LAN, Remote Monitoring by network, 4 Alarm inputs, 1 ala
GV-EM412DD-250	GV-EM412DD with removable 250 GB Hard Drive
STANDALONE DIGITAL VIDEO RECORDERS	
SPR-9816-250	Samsung DVR, 16 Ch, MPEG4 compression, 480 ips record, real time viewing, triplex, 2 USB ports, 16 Ch Audio, 250G Hard drive.
STANDALONE DIGITAL VIDEO RECORDERS	
GV-250GBHD	Additional 250GB fixed hard drive for DVR's, ask for compatibility
GV-500GBHD	Additional 500GB fixed hard drive for DVR's, ask for compatibility

GV-1000GBHD	Additional 1000GB fixed hard drive for DVR's, ask for compatibility
GV-MPG48016AMX	Capture card 480/480 FPS, hardware compression, 16Ch
Edge Devices Hardware	
S1704e-T	DVD-quality Ethernet Video Server with 4 video inputs (12VDC)
S1704e-T-A	DVD-quality Ethernet Video Server with 4 video inputs, 1 bidirectional audio input (12VDC)
S1704e-T-AS	High resolution Ethernet video server (encoder) incl. 4 video inputs (12VDC) with on-board analytics
S1704e-T-AS-A	High resolution Ethernet video server (encoder) with 4 video inputs and 1 bidirectional audio input (12VDC)* Analytics license not included
S1708e-T-AS	DVD-quality Ethernet Video Server with 8 video inputs and on-board analytics (12VDC)* Analytics license not included
S1708e-T-A-AS	DVD-quality Ethernet Video Server with 8 video inputs, 1 bidirectional audio input and on-board analytics (12VDC)* Analytics license not included
S1708e-T	High resolution Ethernet video server (encoder) with 8 video inputs (12VDC)*
S1708e-T-A	High resolution Ethernet video server (encoder) with 8 video inputs and 1 bidirectional audio input (12VDC)*
S1708e-T-12iA	DVD-quality Ethernet video server with 8 video inputs and 12 audio unidirectional inputs (12VDC)
S1712e-T	High resolution Ethernet video server (encoder) with 12 video inputs (12VDC)*
S1712e-T-A	High resolution Ethernet video server (encoder) with 12 video inputs and 1 bidirectional audio input (12VDC)*
S1712e-T-12iA	DVD-quality Ethernet video server with 12 video inputs and 12 audio unidirectional inputs (12VDC)
S1724e-T	High resolution Ethernet video server (encoder) with 24 video inputs (12VDC)*
S1724e-T-A	High resolution Ethernet video server (encoder) with 24 video inputs and 1 bidirectional audio input (12VDC)*
S1900e-Vicon	PCB for Vicon Surveyor/VFT PTZ domes
S1900e-T-AS	Highly compact, DVD-quality Ethernet Video Server with 12VDC Analytics license not included
S1900e-T-AS-XT	Highly compact, DVD-quality Ethernet Video Server with on-board analytics and with extended temperature range (-30/+55°C); 12VDC power supply included Analytics license not included
S1950e-T	Highly compact Ethernet Video Server with 1 bidirectional audio input; 12VDC power supply included
S1950e-T-XT	Highly compact Ethernet Video Server with 1 bidirectional audio input and extended temperature range (-30/+60°C); 12VDC power supply included
S1970e-R-XT	Highly compact, DVD-quality Ethernet Video receiver with 1 bidirectional audio input and extended temperature; 12VDC power supply included
S1970e-R	Highly compact, DVD-quality Ethernet Video receiver with 1 bidirectional audio input; 12VDC power supply included

S1970e-T-Xt	Highly compact, DVD-quality Ethernet Video Server with 1 bidirectional audio input and extended temperature range (-30/+60°C); 12VDC power supply included
S1970e-T-PoE	Highly compact, DVD-quality Ethernet Video Server with 1 audio input and PoE Support (PoE injector not included)
S1970e-T-PoE-Xt	Highly compact, DVD-quality Ethernet Video Server with 1 audio input, PoE (PoE injector not included) and extended temperature range (-30/+50°C)
S2600e	DVD-Quality, super wide dynamic range fixed IP camera; 12VDC (12VDC power supply included)
S2600e-AS	DVD-Quality, super wide dynamic range fixed IP camera with on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2610e	DVD-Quality, Fixed, super wide dynamic range IP camera with day/night support; POE or 12VDC (12VDC power supply included) Analytics license not included
S2610e-AS	Wide dynamic range fixed IP camera with day/night support and on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2600e-L1	DVD-Quality, super wide dynamic range fixed IP camera with lense; 12VDC (12VDC power supply included)
S2600e-AS-L1	DVD-Quality, super wide dynamic range fixed IP camera with lense with on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2610e-L1	DVD-Quality, Fixed, super wide dynamic range IP camera with lense with day/night support; POE or 12VDC (12VDC power supply included) Analytics license not included
S2610e-AS-L1	Wide dynamic range fixed IP camera with lense with day/night support and on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2700e	DVD-Quality, NTSC IP Mini-Dome Camera with Day-to-Night Function; PoE or 12VDC (12VDC power supply included)
S2700e-VR	DVD-quality, vandal-resistant IP mini-dome camera with Day-to-Night function; POE injector sold separately
S2700e-VR-Xt	DVD-quality, vandal-resistant IP mini-dome camera with Day-to-Night function and extended temperature (-30°C to 50°C, w/heater); POE injector sold separately
S2700eP	DVD-quality, PAL IP mini-dome camera with day-to-night function; PoE or 12VDC (12VDC power supply included)
S2700eP-VR	DVD-quality, vandal-resistant PAL IP mini-dome camera with Day-to-Night function; PoE or 12VDC (12VDC power supply included)
S2700eP-VR-Xt	DVD-quality, vandal-resistant PAL IP mini-dome camera with Day-to-Night function and extended temperature (-30°C to 50°C, w/heater); PoE or 12VDC and 24VAC for the heater (12VDC and 24VAC power supplies are included)
S2750ePc	Fixed Dome IP Camera (PAL), Clear Cover
S2750ePs	Fixed Dome IP Camera (PAL), Smoked Cover
S2750eNc	Fixed Dome IP Camera (NTSC), Clear Cover
S2750eNs	Fixed Dome IP Camera (NTSC), Smoked Cover
S4100	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter/Receiver with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC)
S4100-2V	Outdoor Multi-band 2.4/5GHz Transmitter/Receiver with two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America **
S4200	Outdoor Multi-band 2.4/5GHz Transmitter with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **
S4200-CE	Outdoor Multi-band 2.4/5GHz Transmitter for Europe with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **

S4200-2V	Outdoor Multi-band 2.4/5GHz Transmitter with two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-2V-CE	Outdoor Multi-band 2.4/5GHz Transmitter for Europe with two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-AS-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with on-board analytics* and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America **
S4200-AS	Outdoor Multi-band 2.4 GHz/5GHz Transmitter with on-board analytics* and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **
S4200-AS-CE	Outdoor Multi-band 2.4 GHz/5GHz Transmitter for Europe with on-board analytics* and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **
S4200-AS-2V-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with on-board analytics*, two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America
S4200-AS-2V	Outdoor Multi-band 2.4 GHz/5GHz Transmitter with on-board analytics*, two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-AS-2V-CE	Outdoor Multi-band 2.4 GHz/5GHz Transmitter for Europe with on-board analytics*, two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
For APAC Only	
S1704e-T	DVD-quality Ethernet Video Server with 4 video inputs (12VDC)
S1704e-T-A	DVD-quality Ethernet Video Server with 4 video inputs, 1 bidirectional audio input (12VDC)
S1704e-T-AS	High resolution Ethernet video server (encoder) incl. 4 video inputs (12VDC) with on-board analytics
S1704e-T-AS-A	High resolution Ethernet video server (encoder) with 4 video inputs and 1 bidirectional audio input (12VDC)* Analytics license not included
S1708e-T-AS	DVD-quality Ethernet Video Server with 8 video inputs and on-board analytics (12VDC)* Analytics license not included
S1708e-T-A-AS	DVD-quality Ethernet Video Server with 8 video inputs, 1 bidirectional audio input and on-board analytics (12VDC)* Analytics license not included
S1708e-T	High resolution Ethernet video server (encoder) with 8 video inputs (12VDC)*
S1708e-T-A	High resolution Ethernet video server (encoder) with 8 video inputs and 1 bidirectional audio input (12VDC)*
S1708e-T-12iA	DVD-quality Ethernet video server with 8 video inputs and 12 audio unidirectional inputs (12VDC)
S1712e-T	High resolution Ethernet video server (encoder) with 12 video inputs (12VDC)*
S1712e-T-A	High resolution Ethernet video server (encoder) with 12 video inputs and 1 bidirectional audio input (12VDC)*
S1712e-T-12iA	DVD-quality Ethernet video server with 12 video inputs and 12 audio unidirectional inputs (12VDC)
S1724e-T	High resolution Ethernet video server (encoder) with 24 video inputs (12VDC)*
S1724e-T-A	High resolution Ethernet video server (encoder) with 24 video inputs and 1 bidirectional audio input (12VDC)*
S1900e-Vicon	PCB for Vicon Surveyor/VFT PTZ domes
S1900e-T-AS	Highly compact, DVD-quality Ethernet Video Server with 12VDC Analytics license not included
S1900e-T-AS-XT	Highly compact, DVD-quality Ethernet Video Server with on-board analytics and with extended temperature range (-30/+55°C); 12VDC power supply included Analytics license not included

S1950e-T-XT	Highly compact Ethernet Video Server with 1 bidirectional audio input and extended temperature range (-30/+60°C); 12VDC power supply included
S1970e-R-XT	Highly compact, DVD-quality Ethernet Video receiver with 1 bidirectional audio input and extended temperature; 12VDC power supply included
S1970e-R	Highly compact, DVD-quality Ethernet Video receiver with 1 bidirectional audio input; 12VDC power supply included
S1970e-T	Highly compact, DVD-quality Ethernet Video Server with 1 bidirectional audio input; 12VDC power supply included
S1970e-T-XT	Highly compact, DVD-quality Ethernet Video Server with 1 bidirectional audio input and extended temperature range (-30/+60°C); 12VDC power supply included
S1970e-T-PoE	Highly compact, DVD-quality Ethernet Video Server with 1 audio input and PoE Support (PoE injector not included)
S1970e-T-PoE-XT	Highly compact, DVD-quality Ethernet Video Server with 1 audio input, PoE (PoE injector not included) and extended temperature range (-30/+50°C)
S2600e	DVD-Quality, super wide dynamic range fixed IP camera; 12VDC (12VDC power supply included)
S2600e-AS	DVD-Quality, super wide dynamic range fixed IP camera with on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2610e	DVD-Quality, Fixed, super wide dynamic range IP camera with day/night support; POE or 12VDC (12VDC power supply included) Analytics license not included
S2610e-AS	Wide dynamic range fixed IP camera with day/night support and on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2600e-L1	DVD-Quality, super wide dynamic range fixed IP camera with lense; 12VDC (12VDC power supply included)
S2600e-AS-L1	DVD-Quality, super wide dynamic range fixed IP camera with lense with on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2610e-L1	DVD-Quality, Fixed, super wide dynamic range IP camera with lense with day/night support; POE or 12VDC (12VDC power supply included) Analytics license not included
S2610e-AS-L1	Wide dynamic range fixed IP camera with lense with day/night support and on-board analytics; 12VDC (12VDC power supply included) Analytics license not included
S2700e	DVD-Quality, NTSC IP Mini-Dome Camera with Day-to-Night Function; PoE or 12VDC (12VDC power supply included)
S2700e-VR	DVD-quality, vandal-resistant IP mini-dome camera with Day-to-Night function; POE injector sold separately
S2700e-VR-XT	DVD-quality, vandal-resistant IP mini-dome camera with Day-to-Night function and extended temperature (-30°C to 50°C, w/heater); POE injector sold separately
S2700eP	DVD-quality, PAL IP mini-dome camera with day-to-night function; PoE or 12VDC (12VDC power supply included)
S2700eP-VR	DVD-quality, vandal-resistant PAL IP mini-dome camera with Day-to-Night function; PoE or 12VDC (12VDC power supply included)
S2700eP-VR-XT	DVD-quality, vandal-resistant PAL IP mini-dome camera with Day-to-Night function and extended temperature (-30°C to 50°C, w/heater); PoE or 12VDC and 24VAC for the heater (12VDC and 24VAC power supplies are included)
S2750ePc	Fixed Dome IP Camera (PAL), Clear Cover
S2750ePs	Fixed Dome IP Camera (PAL), Smoked Cover
S2750eNc	Fixed Dome IP Camera (NTSC), Clear Cover
S2750eNs	Fixed Dome IP Camera (NTSC), Smoked Cover
S4200-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America **

S4200-CE	Outdoor Multi-band 2.4/5GHz Transmitter for Europe with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **
S4200-2V-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America
S4200-2V	Outdoor Multi-band 2.4/5GHz Transmitter with two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-2V-CE	Outdoor Multi-band 2.4/5GHz Transmitter for Europe with two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-AS-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with on-board analytics* and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America **
S4200-AS	Outdoor Multi-band 2.4 GHz/5GHz Transmitter with on-board analytics* and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **
S4200-AS-CE	Outdoor Multi-band 2.4 GHz/5GHz Transmitter for Europe with on-board analytics* and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC) **
S4200-AS-2V-49	Outdoor Multi-band 2.4 GHz/4.9GHz/5GHz Transmitter with on-board analytics*, two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 4.9GHz/5 GHz antenna (12VDC/24VAC) North America
S4200-AS-2V	Outdoor Multi-band 2.4 GHz/5GHz Transmitter with on-board analytics*, two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
S4200-AS-2V-CE	Outdoor Multi-band 2.4 GHz/5GHz Transmitter for Europe with on-board analytics*, two video inputs and with integrated 8.5 dBi, 2.4 GHz antenna and 12 dBi, 5 GHz antenna (12VDC/24VAC)
on IP PTZ cameras and accessories	
S2800eN-C22CA	In-ceiling, color IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, housing, 22X high-resolution color camera/lens, and smoked lower dome
S2800eN-P22CA	Indoor/pendant, color IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, housing, 22X high-resolution color camera/lens, and smoked lower dome
S2800eN-W22CA	Outdoor, color IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, environmental housing, 22X high-resolution color camera/lens and clear outer dome
S2800eN-C22	Indoor/in-ceiling, color IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, in-ceiling metal housing, 22X high-sensitivity high-resolution color camera/lens with ExView™ technology and smoked lower dome
S2800eN-P22	Indoor/pendant, color IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive; pendant upper housing, 22X high-sensitivity high-resolution color camera/lens with ExView™ technology and smoked lower dome
S2800eN-W22	Outdoor, color IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, environmental housing, 22X high-sensitivity high-resolution color camera/lens with ExView™ technology and clear outer dome
S2800eN-C23	Indoor in-ceiling, day/night IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, in-ceiling metal housing, 23X day/night camera/lens with wide dynamic range and smoked lower dome
S2800eN-P23	Indoor pendant, day/night IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, pendant upper housing, 23X day/night camera/lens with wide dynamic range and smoked lower dome
S2800eN-W23	Outdoor, day/night IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, environmental housing, 23X day/night camera/lens with wide dynamic range and clear outer dome
S2800eN-W35	Outdoor, day/night IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, environmental housing, 35X high-resolution day/night camera/lens with wide dynamic range and image stabilization and clear outer dome
S2800eN-M23	Impact Resistant, day/night IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, environmental housing, 23X high-resolution day/night camera/lens with wide dynamic range and clear outer dome

S2800eN-M35	Impact Resistant, day/night IP dome; 4CIF/30 FPS MPEG4/MJPEG compressions, includes variable-speed drive, environmental housing, 35X high-resolution day/night camera/lens with wide dynamic range and image stabilization and clear outer dome
V-UWM	Wall mount, indoor/outdoor
V-UCM	Ceiling mount, indoor/outdoor
V-UPM-1	Parapet mount, outdoor
V-URM-1	Roof mount, outdoor
V-UCP	Ceiling panel, indoor
V-WM	Wall mount, short, indoor/outdoor
V-IC-MKT	In-ceiling mount kit, indoor
S28PS-1	28 VAC output, 2.15 amps, for indoor S2800e Camera Domes
S28WPS-1	28 VAC output, 3 amps, for outdoor S2800e Camera Domes
Encoder and IP Camera Accessories	
VRM8	Standard black anodized 19 inch rack mount panel for 8 units of the Nextiva S1900e series (S1950e-T, S1970e-T/R, S1900e-T-AS)
CLRDOME	Clear dome cover for S2700e IP mini dome camera
POE	Power over Ethernet Injector for the S2600e fixed IP camera series and the S27xxe IP mini dome and S1970e-T-POE with US power cord
POE-UK	Power over Ethernet Injector for the S2600e fixed IP camera series and the S27xxe IP mini dome and S1970e-T-POE with UK power cord
POE-EU	Power over Ethernet Injector for the S2600e fixed IP camera series and the S27xxe IP mini dome and S1970e-T-POE EU power cord
PS12	Power supply 100-240VAC to 12VDC with 1.25 A for one (1) 12VDC wireless device or S2750e IP Camera; North America/Europe/United Kingdom; NOT OUTDOOR; UL; ROHS
PS1260	110VAC to 12VDC at 45W transformer for (1) one S1504/1508/1704/1708/1712/1724 series
PS1260-GM	110/230VAC to 12VDC at 45W transformer for (1) one S1504/1508/1704/1708/1712/1724 series with European power cord
PS1260-UK	110/230VAC to 12VDC at 45W transformer for (1) one S1504/1508/1704/1708/1712/1724 series with UK power cord
PS1281	19-inch rack mountable power supply 110V AC to dual 14V DC with 23 A, for ten (10) S1704e/S1708e/S1712e/S1724e devices. Recommended with PDP10-2; North America; ROHS
PS1281-EU	19-inch rack mountable power supply 230V AC to dual 14V DC with 23 A, for ten (10) S1704e/S1708e/S1712e/S1724e devices. Recommended with PDP10-2; Europe & UK; ROHS
PDP10-2	19-inch 1U power distribution panel rack mount to connect up to ten (10) S1704e/S1708e/S1712e/S1724e devices (requires the purchase of a PS1281)
Additional Accessories for S4200 Series	

PS2440-UK	Power supply; 220V IN; 24VAC OUT; 1.5A; 50Hz; DESKTOP (BUILT-IN POWER CORD); United Kingdom; CE, GS; ROHS
PS2440-EU	Power supply; 220V IN; 24VAC OUT; 1.5A; 50Hz; DESKTOP (BUILT-IN POWER CORD); Europe; CE, ROHS
CABPV	Spare 3 meter (10-foot) cabling assembly for power/video/PTZ
CABAA	Audio and Alarms Cable
S4300 Wireless Bridge	
S4300-PoE-49	Outdoor 2.4 GHz/4.9GHz/5GHz wireless access point (48VDC input) comes with power-over-Ethernet injector and power supply, 82-foot (25-meter) outdoor Ethernet cable, wall-mount and pole-mount brackets and tri-band antenna
S4300-PoE	Outdoor 2.4 GHz/5GHz wireless access point (48VDC input) comes with power-over-Ethernet injector and power supply, 82-foot (25-meter) outdoor Ethernet cable, wall-mount and pole-mount brackets and tri-band antenna
S4300-PoE-CE	Outdoor 2.4 GHz/5GHz wireless access point for Europe (48VDC input) comes with power-over-Ethernet injector and power supply, 82-foot (25-meter) outdoor Ethernet cable, wall-mount and pole-mount brackets and tri-band antenna
S4300-PoE-UK	Outdoor 2.4 GHz/5GHz wireless access point for United Kingdom (48VDC input) comes with power-over-Ethernet injector and power supply, 82-foot (25-meter) outdoor Ethernet cable, wall-mount and pole-mount brackets and tri-band antenna
S4300-RP-49	Outdoor 2.4 GHz/4.9GHz/5GHz wireless Ethernet repeater (12VDC/24VAC input) with two 6-foot (2-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and two tri-band antennas
S4300-RP	Outdoor 2.4 GHz/5GHz wireless Ethernet repeater (12VDC/24VAC input) with two 6-foot (2-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and two tri-band antennas
S4300-RP-CE	Outdoor 2.4 GHz/5GHz wireless Ethernet repeater for Europe (12VDC/24VAC input) with two 6-foot (2-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and two tri-band antennas
S4300-BR-49	Outdoor 2.4 GHz/4.9GHz/5GHz wireless Ethernet bridge (12VDC/24VAC input) with two 82-foot (25-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and two tri-band antennas
S4300-BR	Outdoor 2.4 GHz/5GHz wireless Ethernet bridge (12VDC/24VAC input) with two 82-foot (25-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and tri-band antennas
S4300-BR-CE	Outdoor 2.4 GHz/5GHz wireless Ethernet bridge for Europe (12VDC/24VAC input) with two 82-foot (25-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and tri-band antennas
S4300-BR-PoE-49	Outdoor 2.4 GHz/4.9GHz/5GHz wireless Ethernet bridge (48VDC input) comes with two power-over-Ethernet injectors and power supplies, two 82-foot (25-meter) outdoor Ethernet cables, wall-mount and pole-mount brackets and tri-band antennas
S4300-BR-PoE	Outdoor 2.4 GHz/5GHz wireless Ethernet bridge (48VDC input) comes with two power-over-Ethernet injectors and power supplies, two 25-meter outdoor Ethernet cables, wall-mount and pole-mount brackets and tri-band antennas
S4300-BR-PoE-CE	Outdoor 2.4 GHz/5GHz wireless Ethernet bridge for Europe (48VDC input) comes with two power-over-Ethernet injectors and power supplies, two 25-meter outdoor Ethernet cables, wall-mount and pole-mount brackets and tri-band antennas
S4300-BR-PoE-UK	Outdoor 2.4 GHz/5GHz wireless Ethernet bridge for United Kingdom (48VDC input) comes with two power-over-Ethernet injectors and power supplies, two 25-meter outdoor Ethernet cables, wall-mount and pole-mount brackets and tri-band antennas
Accessories for S4200 and S4300 Series	
ANT-WP16-24/S	16dBi gain, 2.4GHz band, 27° beamwidth, patch antenna with 1 meter (3-foot) SMA-N cable
ANT-WS16-5X/S	16dBi gain, 5.25-5.85GHz band, 90° beamwidth, sector panel antenna with 1 meter (3-foot) SMA-N cable
ANT-WP19-5X/S	19dBi gain, 5.25-5.85GHz band, 18° beamwidth, subscriber antenna ; H/V-BW; N female; ROHS
ANT-WP23-5X/S	23 dBi gain, 5.15-5.875 GHz band, 9° beamwidth H/V-MW, subscriber antenna, N female
ANT-WP25-49	ANTENNA; 25dBi; Linear, Flat-panel; 4.9GHz-5.1GHz; 6deg H-BW; N-Type female; ROHS
ANT-WP18-49	ANTENNA; 18dBi; Linear, Flat-panel; 4.9GHz-5.1GHz; 20deg H-BW; N-Type female; ROHS

CABET-25	25 meter (82 foot) outdoor Ethernet replacement cable
CABET-50	50 meter (164 foot) outdoor Ethernet replacement cable
Nextiva S/W	
NEX-5.1-MS-S	Nextiva Master Server software 5.1 DVD with License and Software Protection Key
NEX-5.1-MR-S	Software DVD and License with Protection for Master Recorder 5.1 only
NEX-5.1-1CAM-S	One (1) Camera S/W License
NEX-5.1-1CAMIP-S	One (1) Third party IP Camera S/W License
NEX-5.1-1FOC-S	One (1) Nextiva fail-over camera software license
NEX-5.1-ESM-ST	Enterprise Storage Manager Software - Site License
NEX-5.1-IS-ST	IntelliStream Software
NEX-5.1-1RV-S	One (1) Review/Smart Client License
NEX-5.1-1RV-CFE	One (1) Review/Smart Client License without SQL CAL license
NEX-5.1-RV-ST	Review Site Licenses
NEX-5.1-RV-STCFE	Review Site Licenses without SQL processor licenses
NEX-5.1-AN-E100	IntelliView Analytics (OV 4) Sensor License - E100 Silver
NEX-5.1-AN-E200	IntelliView Analytics (OV 4) Sensor License - E200 gold
NEX-5.1-AN-E1000	IntelliView Analytics (OV 4) Sensor License - E1000 platinum
NEX-5.1-AN-S500	\$500 Server Based Platinum sensor (E-1000 OV 4)
NEX-5.1-FM-S500	Nextiva Flow Monitor Server based
NEX-5.1-AN-FA	IntelliView Forensic Analytics Site License
NEX-5.1-MO-ST	Mosaic S/W and Site License (up to 15 scene stitching)
NEX-5.1-1SDK-S	One (1) SDK Connection License
NEX-5.1-IM-ST	Investigation Management Site License
NEX-5.1-MS-KEY-T	Nextiva software 90 day time Software Key Not for resale to end customer
NEX-5.1-MP-ST	Map Support License
NEX-5.1-MT-ST	MotionTrack – One Input, does not include power supply

NEX-5-MAN-GOLD	Gold Maintenance for Year 1
16-900-0061	NEXTIVA, APAC HASP HL DONGLE KEY
SERVER	
NEX-MS-BR	Master server 2G RAM com Xeon Processor, com Nextiva Master Server software 5.1 DVD with License and Software Protection Key, com SQL Server 2005, 80 Gb em RAD 1, Windows 2003 Server
NEX-MR-BR	Master Recoding, com RAID 5, Wndows XP, 2 GB RAM, expansivel até 4 Tera, com suporte para 96, SQL Cal e Win Cal,
NEX-WK-BR	Workstation, 2 Gb RAM, windows XP, 80 Gb HD, com Nextiva Rewiew - CFE, com SQL Cal licença, suporte a 2 monitores, windows cal.
NEX-IVP-BR	Nextiva analytics server
T-190	Monitor 19 LCD Samsung T190 1440x900 2ms 20000:1 Rose Black (Vermelho) DVI Wide
Acess Control Software	
MDC4WEB-LIGHT	Licença de uso Software Gerenciamento de Acesso mono usuario, para banco de dados SQL, permite gerenciar/controlar até 05 Controladoras MDC4IP
MDC4WEB-FULL	Licença de uso Software Gerenciamento de Acesso multi usuario, para banco de dados SQL/ORACLE, permite gerenciar/controlar até 120 Controladoras, sem limites de usuário para estações de trabalho
MDC4WEB-ALARM	Licença de uso Software Gerenciamento de Acesso multi usuario, para banco de dados SQL/ORACLE, permite gerenciar/controlar até 120 Controladoras, sem limites de usuário para estações de trabalho
MDC4WEB-VISIT	Licença de uso Software multi usuario Gerenciamento e controlador de Visitantes com captura de imagem através de uma Web Cam (Padrão Usb) ou placa de digitalizadora com canais padrão PCI. Permite via rede Ethenert/Web, centralizar banco de fotos em servidor
MDC4WEB-BIO	Licença de uso do Software par biometria
MDC4WEB-FIRM	Licença de uso dos coletores de dados
Acess Control Software	
MDC4IP-GEN	Placa controladora ethernet 10/100Mbps com memoria de 512Kb expansível ate 1Mb, com 5 entradas, 5 saídas de contatos
MDC4IP-TCL	Teclado com display para ativação/desativação de zonas
MC series	
OneVideo	
PICO CAMERA KIT /XX*	1x Miniature transmitter (PICO) and receiver (PICO RX), incl. 1x PSA 12 DC
Europe, US: North America, UK: United Kingdom, AUS: Australia and China.	
PICO	
PICO	Miniature video transmitter

PICO AC-25	PICO adapter cord, BNC male to BNC female, 25cm
VBS 2010 TX	Video transmitter, 850 nm
VBS 2010 RX	Video receiver, 850 nm, Automatic Gain Control
VBS 2020 TX	Matchbox video transmitter, 850 nm
VBS 2020 TX-3	Triple video transmitter, 850 mm, video presence indicator
VBS 2020 RX-3	Triple video receiver, 850 mm, Automatic Gain Control
UTF 4000 TX-MSA	Miniature digital video transmitter with alarm contact
UTF 4000 RX	Digital video receiver with alarm contact
UTF 4000 RX-2	Dual digital video receiver with alarm contact
9000 series	
OneVideo	
9111 DT-L-ST	1-ch. digital video transmitter
9111 DR-L-ST	1-ch. digital video receiver
9111 DRRR-L-ST	Triple channel digital video receiver
9114 DR-L-ST	Compact digital video receiver
Fiber Optic Transmission, multimode (continued)	
MC series	
OneVideoData	
VDS 2200 TX	Matchbox video transmitter, data transceiver, 850 nm
VDS 2200 RX	Video receiver, data transceiver, 850 nm, Automatic Gain Control

UTF 4200 TX -MSA	Miniature digital video transmitter with CC and FDX RS422/485, 2-fibre 1300 nm
UTF 4200 RX	Digital video receiver with CC and 2xFDX RS422/485, 2-fibre 1300 nm
UTF 4200 RX-2	Dual digital video receiver with CC and FDX RS422/485, 2-fibre 1300 nm
UTF 4210 TX -MSA	Miniature digital video transmitter with CC and FDX RS422/485, 1-fibre 1310/1550
UTF 4210 RX	Digital video receiver with CC and FDX RS422/485, 1-fibre 1310/1550
UTF 4210 RX-2	Dual digital video receiver with CC and FDX RS422/485, 1-fibre 1310/1550
UTF 4200 TX -MSA /Bilinx™	Miniature digital video transmitter with CC for Bosch Bilinx™, 2-fibre 1310 nm
UTF 4200 RX /Bilinx™	Digital video receiver with CC for Bosch Bilinx™, 2-fibre 1310 nm
UTF 4200 RX-2 /Bilinx™	Dual digital video receiver with CC for Bosch Bilinx™, 2x 2-fibre 1310 nm
UTF 4210 TX -MSA /Bilinx™	Miniature digital video transmitter with CC for Bosch Bilinx™, 1-fibre 1310/1550
UTF 4210 RX /Bilinx™	Digital video receiver with CC for Bosch Bilinx™, 1-fibre 1310/1550
UTF 4210 RX-2 /Bilinx™	Dual digital video receiver with CC for Bosch Bilinx™, 2x 1-fibre 1310/1550
OneVideoPlus	
VAD 5310 TX	10-Bit digital video transmitter, FDX stereo audio, data & CC's, 850/1300 nm
VAD 5310 RX	10-Bit digital video receiver, FDX stereo audio, data & CC's, 850/1300 nm
9000 series	
OneVideoData	
9221 DT/MMH-ST	1-ch. digital video transmitter, FDX data
9225 DT/MMH-ST	1-ch. digital video transmitter, FDX data
9221 DR/MMH-ST	1-ch. digital video receiver, FDX data

OneVideoData "Pelco"	
9229 DT-P/MMH-ST	In-dome transmitter for Pelco Spectra III
OneVideoData "Up-the-Coax"	
9281 DT/MMH-ST	1-ch. "Up the coax" transmitter
9285 DT/MMH-ST	1-ch. "Up the coax" transmitter
9281 DT-EX/MMH-ST	1-ch. "Up the coax" extended distance transmitter
9281 DR/MMH-ST	1-ch. "Up the coax" receiver
9285 DR/MMH-ST	1-ch. "Up the coax" receiver
9285 DT-EX/MMH-ST	1-ch. "Up the coax" extended distance receiver
OneVideoPlus	
9241 DT(XX)/MMH-ST	1-ch. video transmitter with 3xFDX data/option module channels
9245 DT(XX)/MMH-ST	1-ch. video transmitter with 3xFDX data/option module channels
9241 DR(XX)/MMH-ST	1-ch. video receiver with 3xFDX data/option module channels
9245 DR(XX)/MMH-ST	1-ch. video receiver with 3xFDX data/option module channels
9711 DT-L-ST	1-ch. digital video transmitter with stereo audio
9711 DR-L-ST	1-ch. digital video receiver with stereo audio
9715 DR-L-ST	1-ch. digital video receiver with stereo audio
Fiber Optic Transmission, multimode (continued)	
9000 series	
TwoVideo	
9191 DT-LDS-ST	2-channel digital video transmitter

TwoVideoPlus	
9292 DT(XX)/MMH-ST	2-ch. Digital video TX with 100Mb Ethernet, 1xFDX HS & 2xFDX option module
9292 DR(XX)/MMH-ST	2-ch. Digital video RX with 100Mb Ethernet, 1xFDX HS & 2xFDX option module
9421 DT(XX)/MMH-ST	2-ch. Digital video transmitter with with 1xFDX HS & 2xFDX option module
9421 DR(XX)/MMH-ST	2-ch. Digital video receiver with 1xFDX HS & 2xFDX option module
Fiber Optic Transmission, multimode (continued)	
MC series	
FourVideo	
TETRA 4010 TX	4-ch. digital video multiplexer, 1300 nm
TETRA 4010 RX	4-ch. digital video demultiplexer, 1300 nm
TETRA 5010 TX	4-ch. 10-bit digital video multiplexer, 1300 nm
TETRA 5010 RX	4-ch. 10-bit digital video demultiplexer, 1300 nm
FourVideoData	
TETRA 4210 TX	4-ch. digital video multiplexer with 2-way data, 850/1300 nm
TETRA 4210 RX	4-ch. digital video demultiplexer with 2-way data, 850/1300 nm
TETRA 5210 TX	4-ch. 10-bit digital video multiplexer with FDX data, 850/1300 nm
TETRA 5210 RX	4-ch. 10-bit digital video demultiplexer with FDX data, 850/1300 nm
FourVideoPlus	
TETRA 4310 TX	4-ch. digital video mux with 100Mb Ethernet, FDX stereo audio, data & CC's

TETRA 5310 TX	4-ch. 10-bit video multiplexer with 2-way stereo audio, multiple data and CC's
TETRA 5310 RX	4-ch. 10-bit video demultiplexer with 2-way stereo audio, multiple data and CC's
9000 series	
FourVideo	
9131 DT-LDL-ST	4-ch. 10-bit video multiplexer
9131 DR-LM-ST	4-ch. 10-bit video demultiplexer
FourVideoData	
9341 DT-LDL-ST	4-ch. Digital video multiplexer with 1 simplex HS
9341 DR-LM-ST	4-ch. Digital video demultiplexer with 1 simplex HS
9231 DT/MMH-ST-1315	4-ch. 10-bit video multiplexer with 3xFDX option module
9231 DR/MMH-ST-1513	4-ch. 10-bit video demultiplexer with 3xFDX option module
9442 DT/MMH-ST-1315	4-ch. digital video multiplexer with 1xFDX HS and 2xFDX data
9442 DR/MMH-ST-1513	4-ch. digital video demultiplexer with 1xFDX HS & 2xFDX data
FourVideoPlus	
9432 DT(XXXX)/MMH-ST-1315	4-ch. 10-bit video multiplexer with 3xFDX data ch. & 4xFDX option module ch.
9432 DR(XXXX)/MMH-ST-1513	4-ch. 10-bit video demultiplexer with 3xFDX data ch. & 4xFDX option module ch.
Fiber Optic Transmission, multimode (continued)	
MC series	

OCTA 4010 TX	8-ch. digital video multiplexer, 1300 nm
OCTA 4010 RX	8-ch. digital video demultiplexer, 1300 nm
OCTA 5010 TX	8-ch. 10-bit video multiplexer, 1300 nm
OCTA 5010 RX	8-ch. 10-bit video demultiplexer, 1300 nm
EightVideoPlus	
OCTA 4310 TX	8-ch. digital video mux with 100Mb Ethernet, 2-way stereo audio, data and CC's
OCTA 4310 RX	8-ch. digital video demux with 100Mb Ethernet, 2-way stereo audio, data and CC's
9000 series	
EightVideo	
9152 DT-LDL-ST	8-ch. 10-bit video multiplexer with 2 simplex HS and 3 simplex data
9152 DR-LM-ST	8-ch. 10-bit video demultiplexer with 2 simplex HS and 3 simplex data
EightVideoPlus	
9252 DT/MMH-ST-1315	8-ch. digital video multiplexer with 2 duplex HS and 3 duplex data
9252 DR/MMH-ST-1513	8-ch. digital video demultiplexer with 2xFDX HS & 3xFDX data
Point Fiber Optic Transmission, singlemode	
MC series	
OneVideo	
VBS 2050 TX	Matchbox video transmitter, 1300 nm
VBS 2050 TX-3	Triple video transmitter, 1300 nm, video presence indicator
VBS 2050 RX-3	Triple video receiver, 1300 nm, Automatic Gain Control

UTF 4040 TX-MSA	Miniature digital video transmitter with alarm contact SM 23 dB
UTF 4040 RX	Digital video receiver with alarm contact SM 23 dB
UTF 4040 RX-2	Dual digital video receiver with alarm contact SM 23 dB
9000 series	
OneVideo	
9111 DT-LD-ST	1-ch. digital video transmitter
9111 DTTT-LD-ST	Triple ch. digital video transmitter
9111 DRRR-L-ST	Triple ch. digital video receiver
9114 DR-L-ST	Compact digital video receiver
ber Optic Transmission, singlemode (continued)	
MC series	
OneVideoData	
UTF 4240 TX-MSA	Miniature digital video transmitter with alarm contact SM 23 dB
UTF 4240 RX	Digital video receiver with alarm contact SM 23 dB
UTF 4240 RX-2	Dual digital video receiver with alarm contact SM 23 dB
UTF 4250 TX-MSA	Miniature digital video transmitter with CC and FDX RS422/485, 1-fibre 1310/1550
UTF 4250 RX	Digital video receiver with CC and FDX RS422/485, 1-fibre 1310/1550
UTF 4250 RX-2	Dual digital video receiver with CC and FDX RS422/485, 1-fibre 1310/1550
UTF 4250 TX-MSA /Bilinx™	Miniature digital video transmitter with CC for Bosch Bilinx™, 1-fibre 1310/1550
UTF 4250 RX /Bilinx™	Digital video receiver with CC for Bosch Bilinx™, 1-fibre 1310/1550
UTF 4250 RX-2 /Bilinx™	Dual digital video receiver with CC for Bosch Bilinx™, 2x 1-fibre 1310/1550

UTF 4250 TX/BOSCH	Bosch Dome digital video TX incl bracket with CC & PTZ, 1-fibre 1310/1550
OneVideoPlus	
VAD 5350 TX	Digital video transmitter, with FDX stereo audio, data & CC's, 1310/1550 nm
VAD 5350 RX	Digital video receiver, with FDX stereo audio, data & CC's, 1310/1550 nm
9000 series	
OneVideoData	
9221 DT/SM-ST	1-ch. digital video transmitter, FDX data
9225 DT/SM-ST	1-ch. digital video transmitter, FDX data
9221 DR/SM-ST	1-ch. digital video receiver, FDX data
9225 DR/SM-ST	1-ch. digital video receiver, FDX data
OneVideoData "Pelco"	
9229 DT-P/SM-ST	In-dome transmitter for Pelco Spectra III
OneVideoData "Up-the-Coax"	
9281 DT/SM-ST	1-ch. "Up the coax" transmitter
9281 DT-EX/SM-ST	1-ch. "Up the coax" extended distance transmitter
9285 DT/SM-ST	1-ch. "Up the coax" transmitter
9285 DT-EX/SM-ST	1-ch. "Up the coax" extended distance transmitter
9281 DR/SM-ST	1-ch. "Up the coax" receiver
9285 DR/SM-ST	1-ch. "Up the coax" receiver
OneVideoPlus	

9245 DT(XX)/SM-ST	1-ch. video transmitter with 3xFDX data/option module channels
9241 DR(XX)/SM-ST	1-ch. video receiver with 3xFDX data/option module channels
9245 DR(XX)/SM-ST	1-ch. video receiver with 3xFDX data/option module channels
9711 DT-LD-ST	1-ch. digital video transmitter with stereo audio
9715 DT-LD-ST	1-ch. digital video receiver with stereo audio
9711 DR-L-ST	1-ch. digital video receiver with stereo audio
9715 DR-L-ST	1-ch. digital video receiver with stereo audio
ber Optic Transmission, singlemode (continued)	
9000 series	
TwoVideo	
9191 DT-LD-ST	2-channel digital video transmitter
9191 DR-L-ST	2-channel digital video receiver
TwoVideoPlus	
9292 DT(XX)/SM-ST	2-ch. Digital video TX with 100Mb Ethernet, 1xFDX HS & 2xFDX option module
9292 DT(XX)/SMH-ST	2-ch. Digital video transmitter with 1xFDX HS & 2xFDX option module
9292 DR(XX)/SM-ST	2-ch. Digital video RX with 100Mb Ethernet, 1xFDX HS & 2xFDX option module
9292 DR(XX)/SMH-ST	2-ch. Digital video receiver with 1xFDX HS & 2xFDX option module
9421 DT(XX)/SM-ST	2-ch. Digital video transmitter with 1xFDX HS & 2xFDX option module
9425 DT(XX)/SM-ST	2-ch. Digital video transmitter with 1xFDX HS & 2xFDX option module
9421 DR(XX)/SM-ST	2-ch. Digital video receiver with 1xFDX HS & 2xFDX option module
9425 DR(XX)/SM-ST	2-ch. Digital video receiver with 1xFDX HS & 2xFDX option module

MC series	
FourVideo	
TETRA 4050 TX	4-ch. digital video multiplexer, 1300 nm
TETRA 4050 RX	4-ch. digital video demultiplexer, 1300 nm
TETRA 5050 TX	4-ch. digital video multiplexer, 1310 nm
TETRA 5050 RX	4-ch. digital video demultiplexer, 1310 / 1550 nm
FourVideoData	
TETRA 4250 TX	4-ch. digital video multiplexer with 2-way data, 850/1300 nm
TETRA 4250 RX	4-ch. digital video demultiplexer with 2-way data, 850/1300 nm
TETRA 5250 TX	4-ch. digital video multiplexer with FDX data, 1310/1550 nm
TETRA 5250 RX	4-ch. digital video demultiplexer with FDX data, 1310/1550 nm
FourVideoPlus	
TETRA 4350 TX	4-ch. digital video mux with 100Mb Ethernet, FDX stereo audio, data & CC's
TETRA 4350 RX	4-ch. digital video demux with 100Mb Ethernet, FDX stereo audio, data & CC's
TETRA 5350 TX	4-ch. digital video multiplexer, 2-way stereo audio, multiple data and CC's, 1310/1550 nm
TETRA 5350 RX	4-ch. digital video demultiplexer with 2-way stereo audio, multiple data and CC's, 1310/1550 nm
9000 series	
FourVideo	

9131 DR-L-ST	4-ch. 10-bit video demultiplexer
9341 DT-LD-ST	4-ch. Digital video multiplexer with 1 simplex HS
9341 DR-L-ST	4-ch. Digital video demultiplexer with 1 simplex HS
FourVideoData	
9231 DT/SM-ST-1315	4-ch. 10-bit video multiplexer with 3xFDX option module
9231 DR/SM-ST-1513	4-ch. 10-bit video demultiplexer with 3xFDX option module
9442 DT/SM-1315	4-ch. digital video multiplexer with 1xFDX HS & 2xFDX data
9442 DT/SMH-ST-1513	4-ch. digital video multiplexer extended range with 1xFDX HS & 2xFDX data
9442 DR/SM-ST-1513	4-ch. digital video demultiplexer with 1xFDX HS & 2xFDX data
9442 DR/SMH-ST-1315	4-ch. digital video demultiplexer extended range with 1xFDX HS & 2xFDX data
FourVideoPlus	
9432 DT(XXXX)/SM-ST-1315	4-ch. 10-bit video multiplexer with 3xFDX data & 4xFDX option module
9432 DT(XXXX)/SMH-ST-1513	4-ch. 10-bit video multiplexer ext. range with 3xFDX data & 4xFDX option module
9432 DR(XXXX)/SM-ST-1513	4-ch. 10-bit video demultiplexer with 3xFDX data & 4xFDX option module
9432 DR(XXXX)/SMH-ST-1315	4-ch. 10-bit video demultiplexer ext. with 3xFDX data & 4xFDX option module
ber Optic Transmission, singlemode (continued)	
MC series	
EightVideo	
OCTA 4050 TX	8-ch. digital video multiplexer, 1300 nm
OCTA 4050 RX	8-ch. digital video demultiplexer, 1300 nm

OCTA 6050 TX/HP	8-ch. digital video multiplexer, single wavelength, 1310nm, high-power
OCTA 6050 RX	8-ch. digital video demultiplexer, 1310 nm
EightVideoPlus	
OCTA 4350 TX	8-ch. digital video mux with 100Mb Ethernet, 2-way stereo audio, data and CC's, 850/1300 nm
OCTA 4350 RX	8-ch. digital video demux with 100Mb Ethernet, 2-way stereo audio, data and CC's, 850/1300 nm
9000 series	
EightVideo	
9152 DT-L-ST	8-ch. 10-bit video multiplexer with 2 simplex HS and 3 simplex data
9152 DR-L-ST	8-ch. 10-bit video demultiplexer with 2 simplex HS and 3 simplex data
EightVideoPlus	
9252 DT/SM-ST-1315	8-ch. digital video multiplexer with 2 duplex HS and 3 duplex data
9252 DT/SMH-ST-1513	8-ch. digital video multiplexer with 2 duplex HS and 3 duplex data
9252 DR/SM-ST-1513	8-ch. digital video demultiplexer with 2 duplex HS and 3 duplex data
9252 DR/SMH-ST-1315	8-ch. digital video demultiplexer with 2 duplex HS and 3 duplex data
ber Optic Transmission, singlemode (continued)	
9000 series	
Multi-channel solutions	
SpectraStream-16-FC	16-ch. Video transmission system with simplex data
SpectraStream-32-FC	32-ch. Video transmission system with simplex data
SpectraStream-48-FC	48-ch. Video transmission system with simplex data
SpectraStream-64-FC	64-ch. Video transmission system with simplex data

SpectraStream-128-FC	128-ch. Video transmission system with simplex data
SpectraStreamPlus-16-FC	16-ch. Video transmission system with duplex data
SpectraStreamPlus-32-FC	32-ch. Video transmission system with duplex data
SpectraStreamPlus-48-FC	48-ch. Video transmission system with duplex data
SpectraStreamPlus-64-FC	64-ch. Video transmission system with duplex data
SpectraStreamPlus-96-FC	96-ch. Video transmission system with duplex data
SpectraStreamPlus-128-FC	128-ch. Video transmission system with duplex data
Data and Audio	
MC series	
Audio, data and contacts	
ADS 1200 TRX	Dual fibre digital stereo audio and data multiplexer, 1300 nm
ADS 1210 TRA	Single fibre digital stereo audio and data multiplexer A-side, 1310/1550 nm
ADS 1210 TRB	Single fibre digital stereo audio and data multiplexer B-side, 1310/1550 nm
ADS 1240 TRX	Dual fibre digital stereo audio and data multiplexer, 1310 nm
ADS 1250 TRA	Single fibre digital stereo audio and data multiplexer A-side, 1310/1550 nm
ADS 1250 TRB	Single fibre digital stereo audio and data multiplexer B-side, 1310/1550 nm
Contacts	
CCM 1010 TX	8 channel multimode Contact Closure transmitter, mm fibre
CCM 1010 RX	8 channel multimode Contact Closure receiver, mm fibre

9000 series	
OneData	
4132B-S-ST	Miniature RS232 serial data transceiver, 850 nm
4185A-S-ST	Miniature RS422/485 serial data transceiver, 850 nm
4132 B-LD-ST	Miniature RS232 serial data transceiver, 1310 nm
4185 A-LD-ST	Miniature RS422/485 serial data transceiver, 1310 nm
9591-S-ST	1-ch. RS232, RS422, RS485 2-/4-wire and manchester data modem
9591-LD-ST	1-ch. RS232, RS422, RS485 2-/4-wire and manchester data modem
Eight Data	
9551-S-ST	8-ch. RS232 data modem
9555-S-ST	8-ch. RS232 data modem
9551-LD-ST	8-ch. RS232 data modem
9555-LD-ST	8-ch. RS232 data modem
9672Y/MM-08T-ST	Optical 8-ch. duplex HS card
9672Y/MM-13T-ST	Optical 8-ch. duplex HS card
9672Y/SM-13T-ST	Optical 8-ch. duplex HS card
9672Y/SM-15T-ST	Optical 8-ch. duplex HS card
9672Y/SMH-13T-ST	Optical 8-ch. duplex HS card, extended range
9672Y/SMH-15T-ST	Optical 8-ch. duplex HS card, extended range

Drop-and-Insert	
9522A-S-ST	2-ch. RS232, RS422 or RS485 drop and insert data modem
9525A-S-ST	1-ch. RS232, RS422 or RS485 drop and insert data modem
9526A-S-ST	2-ch. RS232, RS422 or RS485 drop and insert data modem
9522A-LD-ST	2-ch. RS232, RS422 or RS485 drop and insert data modem
9522AY/SM-ST	2-ch. RS232, RS422 or RS485 drop and insert data modem
9526A-LD-ST	2-ch. RS232, RS422 or RS485 drop and insert data modem
9526AY/SM-FC	2-ch. RS232, RS422 or RS485 drop and insert data modem
Data and Audio (continued)	
9000 series	
Drop-and-Insert	
9525A-LD-ST	1-ch. RS232, RS422 or RS485 drop and insert data modem
9525AY/SM-ST	1-ch. RS232, RS422 or RS485 drop and insert data modem
9621AY(XXXX)/MM-08T-ST	4-ch. Option module host card
9621AY(XXXX)/MM-13T-ST	4-ch. Option module host card
9622AY(XXXXXXXX)MM-08T-ST	8-ch. Option module host card
9622AY(XXXXXXXX)MM-13T-ST	8-ch. Option module host card
9621AY(XXXX)/SM-13T-ST	4-ch. Option module host card
9621AY(XXXX)/SM-15T-ST	4-ch. Option module host card
9622AY(XXXXXXXX)SM-13T-ST	8-ch. Option module host card
9622AY(XXXXXXXX)SM-15T-ST	8-ch. Option module host card

9571LY/MM-08T-ST	Telephone line extender, line end
9571PY/MM-13T-ST	Telephone line extender, phone end
9575PY/MM-13T-ST	Telephone line extender, phone end
Telephone	
9575LY/SM-13T-ST	Telephone line extender, line end
Audio, data and contacts	
9961A-C(XXXX)	High-Speed port expansion card for 4 option modules
9962A-C(XXXXXXXX)	High-Speed port expansion card for 8 option modules
Ethernet products	
MC series	
Mediaconverter	
XNet 1600 MC	10/100 to 100Base-FX media converter, dual MM, SC, 1300 nm, incl. PSA
XNet 1640 MC	10/100 to 100Base-FX media converter, dual SM, SC, 1310 nm, incl. PSA
XNet 1650 MCA	1-Fibre 10/100 to 100Base-FX media conv., A-side, SM, SC, 1310/1550 nm, incl. PSA
XNet 1650 MCB	1-Fibre 10/100 to 100Base-FX media converter, B-side, SM, SC, 1550/1310 nm, incl. PSA
Unmanaged switch	
XNet 1600 QMC	Fast Ethernet switch with 4x 10/100Mb ports and a 100Mb optical port, MM, 1310 nm
XNet 1640 QMC	Fast Ethernet switch with 4x 10/100Mb ports and a 100Mb optical port, SM, 1310 nm

XSNet 1650 QMCA	Fast Ethernet switch with 4x 10/100Mb ports and a 100Mb optical port, SM, 1310/1550 nm
XSNet 1650 QMCB	Fast Ethernet switch with 4x 10/100Mb ports and a 100Mb optical port, SM, 1550/1310 nm
Managed switch	
XSNet 1800 SW	FE switch with 4x 10/100 Mb ports, 2 pluggable optical 100Mb ports (XSNet SFP)
XSNet 2800 SW	8+2 port field hardened GBE switch, 2 pluggable optical 1000Mb ports (XSNet SFP)
SFP modules	
XSNet SFP MM/850	Multimode SFP, dual-LC connector (100SX/1000FX , 850 nm)
XSNet SFP MM/1310	Multimode SFP, dual-LC connector (100FX, 1300 nm)
XSNet SFP SM/10	Singlemode SFP, dual-LC, 10km
XSNet SFP SM/20	Singlemode SFP, dual-LC, 20km
XSNet SFP SM/60	Long distance singlemode SFP, dual-LC, 60km
XSNet SFP SM/CWDM-X	Coarse-WDM, singlemode SFP, dual-LC connector, l= a,b, ...,h
XSNet SFP SM/BiDiA	Single fibre, singlemode SFP, SC connector, 10km, A-side (1310/1490)
XSNet SFP SM/BiDiB	Single fibre, singlemode SFP, SC connector, 10km, B-side (1490/1310)
9000 series	
Unmanaged switch	
9771-LD-ST	Fast Ethernet Switch with 4x10/100Mb ports and a 100Mb optical port, SM
9771Y/SM-15T-ST	Fast Ethernet Switch with 4x10/100Mb ports and a 100Mb optical port, SM
9971-C	10 BaseT to high-speed port interface card
9973-C	10 BaseT to high-speed port interface card with build-in ethernet switch
Accessories	

9942A	Network Management card
SNM Connection Kit	SNM Configuration and Service Tool on CD-ROM, including RS232-422 data converter and EB-2 connection cord
9900 NMS Software	Software package for Network Management
Power supplies	
19" rack-mount	
MT 03	19" Mounting Tray for 3 SA units
MC 11 AC-230	Power supply cabinet, 19"/3HU, max. 11 modules, 230 Vac
MC 11 AC-230 /EB2	MC 11 AC-230 with SNM (EB2) management interface
MC 11 AC-115	Power supply cabinet, 19"/3HU, max. 11 modules, 115 Vac
MC 11 AC-115 /EB2	MC 11 AC-115 with SNM (EB2) management interface
MC 10 AC-230 /EB2	Dual power supply version with SNM management interface, 230 Vac
MC 10 AC-115 /EB2	Dual power supply version with SNM management interface, 115 Vac
BF 07	7TE blind frontplate for MC series power cabinet
9002	21-slot 19" rack-mount chassis (without power supply unit, 9050BF)
9008	8-slot 2RU 19" rack-mount power supply cabinet
9050BF	3-slot power supply unit for use with the 9002 chassis
9996	Single Blank Panel (1-slot cover plate)
9998	Triple Blank Panel (3-slot cover plate)
Stand-alone housing	
SA	Stand-alone housing to convert single-cassette MC series rack-mount cards
SA2	Stand-alone housing to convert dual-cassette MC series rack-mount cards
MB DINrail	Mounting Bracket for DIN-rail mounting of SA units

Power adapters	
PSA 12 DC/EU	Power adapter, 230 Vac, 12 Vdc, 0,8 A, European plug
PSA 12 DC/UK	Power adapter, 230 Vac, 12 Vdc, 0,8 A, UK plug
PSA 12 DC/USA	Power adapter, 230 Vac, 12 Vdc, 0,8 A, USA plug
PSA 12 DC/AUS	Power adapter, 230 Vac, 12 Vdc, 0,8 A, Australian/Chinese plug
PSA 12 DC-25/EU	Switch-mode power adapter, 230 Vac, 12 Vdc, 1.25 A, European plug
PSA 12 DC-25/UK	Switch-mode power adapter, 230 Vac, 12 Vdc, 1.25 A, UK plug
PSA 12 DC-25/USA	Switch-mode power adapter, 115 Vac, 12 Vdc, 1.25 A, USA plug
PSA 12 DC-25/AUS	Switch-mode power adapter, 230 Vac, 12 Vdc, 1.25 A, Australian/Chinese plug
PSR 12 DC	Power supply unit, rail-mount, 85 to 265 Vac, 12 Vdc/1.5 A
9010PS	Power adapter, 110-220 Vac, 6 Vdc, 4 A, USA plug
9011PS	Power adapter, 110-220 Vac, 12 Vdc, 1 A, USA plug
9014PS	Power adapter, 110 Vac, 9 Vdc, 600 mA, USA plug
Accessories (continued)	
Option modules	
Options modules	
Option Module A	Audio Module
Option Module B	Data Module
Option Module C	Contact Closure Module
Option Module D	Simplex Stereo Audio input Module
Option Module E	Simplex Stereo Audio output Module
Option Module GM	Aiphone Intercom Master End Module
Option Module GR	Aiphone Intercom Remote End Module

DW-Pro-70120	4ch, 30 Frames, PC based DVR, 120 GB, CD-RW, Desktop
DW-Pro-70250	4ch, 30 Frames, PC based DVR, 250 GB, CD-RW, Rack mount (Black color)
DW-Pro-70500	500GB, Rack mount (Black color)
DW-Pro-70750	750GB, Rack mount (Black color)
DW-Pro-71120D-8CH	8ch, 60 Frames, PC based DVR, 120 GB, CD-RW, Desktop
DW-Pro-71250D-8CH	250GB, Desktop
DW-Pro-71500D-8CH	500GB, Desktop
DW-Pro-71750-8CH	750GB, Desktop
DW-Pro-71120D	16ch Video recording, 2ch audio recording, 60fps, 120GB, CD-RW, Desktop.
DW-Pro-71250D	250GB, Desk Top
DW-Pro-71500D	500GB, Desk Top
DW-Pro-71120	16ch Video recording, 2ch audio recording, 60fps, 120GB, CD-RW, Rack mount capable
DW-Pro-71250	250GB
DW-Pro-71500	500GB
DW-Pro-71750	750GB
DW-Pro-71000	1000GB
DW-Pro-711250	1250GB
DW-Pro-711500	1500GB
DW-Pro-711750	1750GB
DW-Pro-712000	2000GB
DW-Pro-712500	2500GB
DW-Pro-72120	16ch Video recording, 2ch audio recording, 120fps, 120GB, CD-RW, Rack mount capable
DW-Pro-72250	250GB
DW-Pro-72500	500GB
DW-Pro-72750	750GB
DW-Pro-721000	1.0 Terabyte

DW-Pro-721500	1.5 Terabyte
DW-Pro-721750	1.75 Terabyte
DW-Pro-722000	2.0 Terabyte
DW-Pro-722500	2.5 Terabyte
DW-Pro-723000	3.0 Terabyte
DW-Pro-723500	3.5 Terabyte
DW-Pro-724000	4.0 Terabyte, 5U chassis
DW-Pro-724500	4.5 Terabyte, 5U chassis
DW-Pro-725000	5.0 Terabyte, 5U chassis
DW-Pro-726000	6.0 Terabyte, 5U chassis
DW-Pro-727500	7.5 Terabyte, 5U chassis
8ch / 240fps Real Time Recorder / Windows 2000	
DW-Pro-9008-120	Hybrid Capable DVR, 8CH Video recording, 4ch audio recording, 240fps, 120GB, DVD-RW, Rack mount capable
DW-Pro-9008-250	250GB
DW-Pro-9008-500	500GB
DW-Pro-9008-750	750GB
DW-Pro-9008-1000	1.0 Terabyte
DW-Pro-9008-1250	1.25 Terabyte
DW-Pro-9008-1500	1.5 Terabyte
DW-Pro-9008-1750	1.75 Terabyte
DW-Pro-9008-2000	2.0 Terabyte
DW-Pro-9008-2500	2.5 Terabyte
DW-Pro-9008-3000	3.0 Terabyte
DW-Pro-9008-3500	3.5 Terabyte
DW-Pro-9008-4000	4.0 Terabyte, 5U chassis
DW-Pro-9008-4500	4.5 Terabyte, 5U chassis

DW-Pro-9008-6000	6.0 Terabyte, 5U chassis
DW-Pro-9008-7500	7.5 Terabyte, 5U chassis
ch / 240fps Digital Video Recorder /Windows 2000	
DW-Pro-9016-120	Hybrid Capable DVR, 16CH Video recording, 4ch audio recording, 240fps, 120GB, DVD-RW, Rack mount capable
DW-Pro-9016-250	250GB
DW-Pro-9016-500	500GB
DW-Pro-9016-750	750GB
DW-Pro-9016-1000	1.0 Terabyte
DW-Pro-9016-1250	1.25 Terabyte
DW-Pro-9016-1500	1.5 Terabyte
DW-Pro-9016-1750	1.75 Terabyte
DW-Pro-9016-2000	2.0 Terabyte
DW-Pro-9016-2500	2.5 Terabyte
DW-Pro-9016-3000	3.0 Terabyte
DW-Pro-9016-3500	3.5 Terabyte
DW-Pro-9016-4000	4.0 Terabyte, 5U chassis
DW-Pro-9016-4500	4.5 Terabyte, 5U chassis
DW-Pro-9016-5000	5.0 Terabyte, 5U chassis
DW-Pro-9016-6000	6.0 Terabyte, 5U chassis
DW-Pro-9016-7500	7.5 Terabyte, 5U chassis
ch / 480fps Digital Video Recorder /Windows 2000	
DW-Pro-9816-120	Hybrid Capable DVR, 16CH Video recording, 4ch audio recording, 480fps, 120GB, DVD-RW, Rack mount capable
DW-Pro-9816-250	250GB
DW-Pro-9816-500	500GB
DW-Pro-9816-750	750GB
DW-Pro-9816-1000	1.0 Terabyte

DW-Pro-9816-1500	1.5 Terabyte
DW-Pro-9816-1750	1.75 Terabyte
DW-Pro-9816-2000	2.0 Terabyte
DW-Pro-9816-2500	2.5 Terabyte
DW-Pro-9816-3000	3.0 Terabyte
DW-Pro-9816-3500	3.5 Terabyte
DW-Pro-9816-4000	4.0 Terabyte, 5U chassis
DW-Pro-9816-4500	4.5 Terabyte, 5U chassis
DW-Pro-9816-5000	5.0 Terabyte, 5U chassis
DW-Pro-9816-6000	6.0 Terabyte, 5U chassis
DW-Pro-9816-7500	7.5 Terabyte, 5U chassis
8ch / 240fps Digital Video Recorder / Windows 2000	
DW-Pro-9032-120	Hybrid Capable DVR, 32CH Video recording, 8ch audio recording, 240fps, 120GB, DVD-RW, Rack mount capable
DW-Pro-9032-250	250GB
DW-Pro-9032-500	500GB
DW-Pro-9032-750	750GB
DW-Pro-9032-1000	1.0 Terabyte
DW-Pro-9032-1250	1.25 Terabyte
DW-Pro-9032-1500	1.5 Terabyte
DW-Pro-9032-1750	1.75 Terabyte
DW-Pro-9032-2000	2.0 Terabyte
DW-Pro-9032-2500	2.5 Terabyte
DW-Pro-9032-3000	3.0 Terabyte
DW-Pro-9032-3500	3.5 Terabyte
DW-Pro-9032-4000	4.0 Terabyte, 5U chassis
DW-Pro-9032-4500	4.5 Terabyte, 5U chassis

DW-Pro-9032-6000	6.0 Terabyte, 5U chassis
DW-Pro-9032-7500	7.5 Terabyte, 5U chassis
ch / 480fps Digital Video Recorder /Windows 2000	
DW-Pro-9832-120	Hybrid Capable DVR, 32CH Video recording, 8ch audio recording, 480fps, 120GB, DVD-RW, Rack mount capable
DW-Pro-9832-250	250GB
DW-Pro-9832-500	500GB
DW-Pro-9832-750	750GB
DW-Pro-9832-1000	1.0 Terabyte
DW-Pro-9832-1250	1.25 Terabyte
DW-Pro-9832-1500	1.5 Terabyte
DW-Pro-9832-1750	1.75 Terabyte
DW-Pro-9832-2000	2.0 Terabyte
DW-Pro-9832-2500	2.5 Terabyte
DW-Pro-9832-3000	3.0 Terabyte
DW-Pro-9832-3500	3.5 Terabyte
DW-Pro-9832-4000	4.0 Terabyte, 5U chassis
DW-Pro-9832-4500	4.5 Terabyte, 5U chassis
DW-Pro-9832-5000	5.0 Terabyte, 5U chassis
DW-Pro-9832-6000	6.0 Terabyte, 5U chassis
DW-Pro-9832-7500	7.5 Terabyte, 5U chassis
Video Management System	
DW-Pro-VMS-SW	Video Management System software
HYBRID DVR License	
DWHY-KIT-4	4ch block of Hybrid License included 4 ports Removable Hard drive Bays
DWHY-LIC-4	4ch block of Hybrid License
DVR/PTZ controller	

DW-PC3001-VB JCT	RS 232 interface junction box between PC3001(DVR keyboard) and DVR
ased DVR POS interface accessories	
DW-POS-DC	1ch POS RS-232 Data stream processor
DW-POS-SI4	4ch POS RS-232 to Network interface
DW-POS-SI2	2ch POS RS-232 to Network interface
DW-POS-SW	POS interface software license (TVS version)
DW-POS-YCB-XXX	Y cable between POS and Cash register
Accessories	
DW-16CHAUD	DW add on 16ch Audio card.
DW-4SERPORT	DW add on 4 port Serial card.
DW-4SPORTM	Programmable 4 spot monitor outputs card fro DW 7000 series
DW-4SPORTM-9000	Programmable 4 spot monitor outputs card for DW 9000 series
DW-4ZA-RECNTR	Universal Remote controller for ZA DVR
DW-AS-GigaNIX	Giga bit Network
DW-DUAL VIEW	Simultaneous display on DVR and TV monitor
DW-DVD/CDRW Combo	DVD RAM and CDRW Combo Drive
DW-FIREWIRE	FIREWIRE CARD
k Video recorder and Video transmitter	
id Digital Video Transmitter products	
DWHVC100	Hybrid IP Camera, MPEG4, 1ch, Video and Audio, 30fps, 720x480
DWNVR-4	Hybrid Digital Video Transmitter, 4ch, MPEG4, 30fps 360x240
DWNVR-4-80G	Hybrid Digital Video Transmitter, 4ch, MPEG4, 30fps 360x240, w/80GB
DWNVR-4-250G	Hybrid Digital Video Transmitter, 4ch, MPEG4, 30fps 360x240, w/250GB
DWHVT301TX	Hybrid Video Transmitter, MPEG4, 1ch, Video and Audio, 30fps, 720x480
DWHVT301TX-40R	40GB
DWHVT301TX-100R	100GB

DWHVT301RX	Hybrid Video Decoder, MPEG4, 1ch, Video and Audio, 30fps, 720x480
DWHVT301TRX	Hybrid Video Encoder and Decoder, MPEG4, 1ch, Video and Audio, 30fps.
DWHVT1204	Hybrid Video Transmitter, MPEG4, 4ch, Video and Audio, 120fps, 360x240
DWHVT1204-40R	40GB
DWHVT1204-100R	100GB
Network Video recorder w/Video manage	
DWNV -64-SW	Software ip recording 64 cam, and dongle key

SEGURANÇA INDUSTRIAL EQUIPAMENTOS - DISTRIBUIDOR AUTORIZADO SAMSUNG NO BRASIL
 home page: www.segind.com.br
 e-mail: cml@segind.com.br
 fone/fax: (41) 3287-1364