

# COMBINATION – BEACON SOUNDER

## EExde, Weatherproof

### CU1 Range



## Introduction

This range of beacon/sounder units, intended for use in potentially explosive gas and dust atmospheres, has a power rating of up to 10 watts (sounder) and 10 joules (beacon) and is suitable for use in the harsh environmental conditions found offshore and onshore in the oil, gas and petrochemical industries.

The flamepaths, flare and body are manufactured from a UV stable glass reinforced polyester. Stainless steel screws and mounting stirrup are incorporated to ensure a corrosion-free product. A tapered flamepath is used to overcome the problems of assembly of parallel spigot flamepaths.

- ★ Zone 1, Zone 2 & non-Ex use.
- ★ EExde IIB T3.
- ★ ATEX approved, Ex II 2 G.
- ★ CENELEC approved.
- ★ GOST 'R' & 'K' Certified.
- ★ BASEEFA certified.
- ★ Brazilian (Inmetro) certified.
- ★ IP66 and 67.
- ★ Certified temperature  $-50^{\circ}\text{C}$  to  $+70^{\circ}\text{C}^*$ .
- ★ Up to 116 dB(A)\*.
- ★ Version with independent beacon/sounder operation now available.
- ★ 27 Tones, user selectable (dual tone option)
- ★ Tones comply with UK00A/PFEER guidelines
- ★ Integral volume control
- ★ GRP corrosion-free flamepath.
- ★ Ratcheted swivel mounting stirrup.
- ★ Stainless steel fixtures.
- ★ Tapered flamepath.

\*Model dependent.

