

KSA701 Series LCD Repeater (mains powered)
KSA701R

The KSA701R repeater allows the user to monitor and control panels connected to the KSA700 fire panel network via an RS485 link. It displays 20 zones in alarm and fault on the face of the panel, whilst all system messages are displayed on the easy to read, LCD display.

Specifications

Supply voltage	
AC version	110 VAC @ 50 Hz or 230 VAC @ 50 Hz (+10% -15%)
DC version	24 VDC
Current consumption	175 mA Quiescent / 200 mA in alarm
Battery charger (AC version only)	
Capacity	2 x 12 V - 7 AH (SLA type)
Fuse rating	3 A
Charger rating	350 mA @ 27.6 VDC @ 20 °C (Temperature compensated -3 V / °C)
Environment	
Working temperature	-5 °C to +40 °C
Relative humidity	95% (non condensing)
IP rating	IP30
Physical characteristics	
Size	420 mm (w) x 335 (h) x 110 (d)
Weight	6.2 kg without batteries / 10.7 kg with 2 x 7 Ah batteries
Communication ports	RS232 and RS485 standard

Ordering Information

KSA701R KSA701 Series LCD Repeater (mains powered)



- Modern, attractive design
- 4 x 40 characters LCD display
- 20 Display zones
- 3 User access levels
- 24 VDC or 230 VAC models available
- Panel networking
- Full system control

Distribuição: Segurança Industrial Equipamentos
 Fone/fax: (41) 4063-9687
cml@segind.com.br - segindbr@hotmail.com
www.segind.com.br