



Conventional fire panel with 4 fire alarm zones

NK704

The NK700 series of conventional fire alarm and extinguishing control panels is the ideal solution for small to medium-sized installations. Very powerful and cost-effective, they are extremely simple to install and use due to their ergonomic, advanced design. The NK704 has 4 conventional zones.

Specifications

Supply voltage	230 VAC @ 50 Hz (±10%)
Batteries	
Capacity	2 x 7.5 Ah
Fuse rating	1 A
Zone	
Maximum load	72 mA
Max number of detectors	20
Sounders	
Maximum load	300 mA
Relay outputs (excluding Sounders)	2 A @ 250 V
Extinguishing relay outputs	
Maximum load	NA
Fuse rating	NA
Open collector outputs	15 mA
Auxilliary output	
Maximum load	300 mA
24 V resetable output	
Maximum load	150 mA
Reset time	4 seconds
Delays	
Sounder selectable	0.15 & 60 s
Relay module	3 to 180 s
Enviroment	
Working temperature	+5°C to +40 °C
Relative humidity	95 % (non-condensing)

Ordering Information

NK704 Conventional fire panel with 4 fire alarm zones



- Modern, attractive design
- Microprocessor-controlled
- From 2 up to 16-zones
- EN54 approved
- 2 User access levels
- 2 Monitored sounder outputs
- One-man test capability
- 24 Volt resetable output
- External 'Class Change' facility
- Alarm output with potential free relay
- Common fault output with potential free relay
- External watchdog
- Active end-of-line support
- Additional optional modules with supervised or relay outputs

Distribuição: Segurança Industrial Equipamentos
 Fone/fax: (41) 4063-9687
 cml@segind.com.br - segindbr@hotmail.com
 www.segind.com.br