



Addressable Relay Module - 4 Relays

KAL434C

Provides for four potential free relay outputs for the fire system loop. Each relay allows for COMMON, NORMALLY OPEN and NORMALLY CLOSED contacts. The outputs may be used to activate ventilation controls, warning signs, activation of other alarm devices etc. during fire situations.

Specifications

Supply voltage	22-38 VDC
Current consumption	
Quiescent @ 24 V	110 A
Quiescent @ 35 V	135 A
Alarm	10 mA
Aux. 24VDC Quiescent	100 A
Aux. 24VDC Alarm	10 mA
End-of-line resistor	NA
Relay contact rating	2½A @ 250 VAC
Environmental	
Storage temperature	-10 to +50°C
Operating temperature	-10 to +70°C
Relative humidity (non-cond.)	0-95 %
Dimensions (l x w x h)	163 x 107 x 36 mm

Ordering Information

KAL434C      Addressable Relay Module - 4 Relays



- Easy numeric addressing
- Externally powered
- Normally open / normally closed operation for I/O
- Surface mount
- Aesthetically pleasing
- Local status indication
- Part of a family of I/O modules consisting of:
  - - Conventional Zone Monitors
  - - Digital Input Modules
  - - Extinguishing Control Modules
  - - Isolator Modules
  - - Manual Call Points
  - - Output Units
  - - Retention Units
  - - Supervised Output Units for sounder control

Distribuição: Segurança Industrial Equipamentos  
Fone/Fax: (41) 4063-9687  
cml@segind.com.br - segindbr@hotmail.com  
www.segind.com.br